


**Name of Work: SUPPLY AND INSTALLTION OF KITCHEN CABINETS,SHUTTERS AND WARDROBES ETC.
FOR BANK's FLATS AT BEGUMPET, HYDERABAD**

BILL OF QUANTITIES

Item No.	Description of work	Estimated Quantity	Unit	Rate	Amount
1	GENERAL WARDROBE WITH MIRROR- DEPTH 550 MM APPROX	160	sqm		
i.	The frame work /carcass of the wardrobes including drawer fascia/ sides/back panel, shelves etc shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) on all sides. Drawer bottom in 12mm thk BWR plywood with ISI mark (IS 303) and Back panels shall be made of 6mm thk BWR plywood with ISI mark (IS 303) and inside laminated with 0.8 mm thk. Laminate of approved make and shade.				
ii.	Shutters shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) of approved make. Each shutter shall be fixed to the framework/ carcass using minimum three numbers of best quality SS Hinges (approved make) and provided with an approved quality and profile brush finished SS handle (minimum 100 mm long)				
iii.	Each drawer made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) will be mounted on approved quality high precision telescopic channels of approved make (to be designed as per drawer size and weight with minimum length of 20") to ensure smooth movements and provided with approved quality SS brush finished handles (minimum 100 mm long).				
iv.	The unit shall be firmly fixed to the walls/ slabs/floor using metal screws of appropriate size and rawplugs/ nylon sleeves.				
v.	All exposed surfaces of the plywood used in the work shall be laminated with 1 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				
vi.	All Inner surfaces of the plywood used in the work shall be suitably polished in minimum two coats whereas the shutters would be laminated with 0.8 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				




vii.	Edges (Top & Bottom) of the plywood shall be provided with 3.0 mm thick teak wood lipping of approved quality and using approved quality and make synthetic resin based adhesives)				
viii	Necessary locks, wall catchers and other accessories for wardrobes viz. Oval pipe/hanger rod etc. to be provided shall be of SS /approved brand. The contractor is also required to provide a bevelled edge mirror of 4 mm thick glass of size 1.35 meter X 0.40 meter fixed with SS studs (Note-Only elevation area will be measured for payment.)				
2	<u>OPENABLE SHUTTERS FOR KITCHEN PLATFORM ,LOFT SLAB, NICHE AREA IN HALL ETC.,</u>	105	sqm		
i.	The frame work shall be made out of 100 mm wide 18/19 mm thick BWR plywood with ISI mark (IS 303) approved make and firmly fixed to the wall/ R.C.C slabs on all sides using appropriate size metal screws, wooden plugs/ nylon sleeves etc as directed.				
ii.	Shutters shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) approved make). Each shutter shall be fixed to the frame work using two or more numbers of best quality SS Hinges (approved make) and provided with an approved quality and profile brush finished SS handle (minimum 100 mm long) and approved make locks, wall catchers wherever required.				
iii.	All exposed surfaces of the plywood used in the work shall be laminated with 1 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				
iv.	All Inner surfaces of the plywood used in the work shall be laminated with 0.8 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives. The work also involved making necessary holes in the shutters for ventilation purpose as directed.				
v.	Edges (Top & Bottom) of the plywood shall be provided with 3.0 mm thick teak wood lipping of approved quality and using approved quality and make synthetic resin based adhesives)				
VI	In case of shelves in Kitchen , the contractor will provide the shutters in the central part with 12 mm BWR Ply plus SS wire mesh of average size of the aperture 1 mm and nominal dia of wire 0.63 mm. Further, the top most shelve will be provided with 5mm thick sliding glass as shown in the drawing (Note only elevation area will be measured for payment)				




	(Note- Only elevation area will be measured for payment.)				
3	OVERHEAD STORAGE UNITS - DEPTH 350 MM APPROX	45	sqm		
i.	CABINETS - The frame work /carcass of the cabinets shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) on all sides. Back panels shall be made of 6mm thk BWR plywood with ISI mark (IS 303) and inside laminated with 0.8mm thk. Laminate of approved make and shade.				
ii.	Shutters shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) and/or with 5 mm thick partly etched glass of approved make. Each shutter shall be fixed to the framework/ carcass using two numbers of best quality EURO type Slip-in Hinges (approved make) and provided with an approved quality and profile brush finished SS handle (minimum 100 mm long) , wall catchers etc.				
iii.	Shelves of the cabinets shall be made out of 8 mm thick clear toughened glass with machine polished edges.				
iv.	All shelves shall be supported on approved quality SS pins and shall be adjustable for various height requirements.				
v.	The unit shall be firmly fixed to the walls/ slabs/floor using metal screws of appropriate size and rawplugs / nylon sleeves.				
vi.	All exposed surfaces of the plywood used in the work shall be laminated with 1 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				
vii.	All Inner surfaces of the plywood used in the work shall be suitably polished in minimum two coats whereas the shutters would be laminated with 0.8 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				
viii.	Edges (Top & Bottom) of the plywood shall be provided with 3.0 mm thick teak wood lipping of approved quality and using approved quality and make synthetic resin based adhesives).				
	(Note-Only elevation area will be measured for payment.)				
4	CROCKERY UNIT-DEPTH 450 MM APPROX (in 3BHK/2BHK Flats)	32	sqm		



i.	The frame work /carcass of the cabinets including drawer fascia/ sides/bottom, shelves (wherever not specified otherwise) etc. shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) on all sides. Back panels shall be made of 6mm thk BWR plywood with ISI mark (IS 303) and inside laminated with 0.8 mm thk. Laminate of approved make and shade.			
ii.	Shelves of the cabinets shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) and/or with 8 mm thick clear toughened glass with machine polished edges.			
iii.	Shutters shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) and/or with 5 mm. thick etched glass of approved make. Each shutter shall be fixed to the framework/ carcass using three numbers of best quality EURO type Slip-in Hinges (approved make) and provided with an approved quality and profile brush finished SS handle of approved design. (minimum 100 mm long), wall catchers etc.			
iv.	Each drawer made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) which shall be mounted on approved quality high precision telescopic channels of approved make (to be designed as per drawer size and weight with minimum length of 18") to ensure smooth movements and provided with approved quality SS brush finished handles (minimum 100 mm long).			
v.	The unit shall be firmly fixed to the walls/ slabs/floor using metal screws of appropriate size and rawplug / nylon sleeves.			
v.	All exposed surfaces of the plywood used in the work shall be laminated with 1 mm thick laminate of approved make and shade (factory pressed) using approved quality and make synthetic resin based adhesives.			
vi.	All Inner surfaces of the plywood used in the work shall be suitably polished in minimum two coats whereas the shutters would be laminated with 0.6 mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.			
vii.	Edges (Top & Bottom) of the plywood shall be provided with 3.0 mm thick teak wood lipping of approved quality and using approved quality and make synthetic resin based adhesives)			




	(Note-This shall be broadly in line with the existing crockery unit / showcase provided in each flat. Only elevation area will be measured for payment).				
5	SHOWCASE IN NICHE AREA OF HALL OF 2 BHK FLATS-600 MM DEPTH APPROX	12	sqm		
i.	The frame work /carcass of the cabinets including drawer fascia/ sides/bottom, shelves (wherever not specified otherwise) etc. shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) on all sides. Back panels shall be made of 6mm thk BWR plywood with ISI mark (IS 303) and inside laminated with 0.8 mm thk. Laminate of approved make and shade.				
ii.	Shelves of the cabinets shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) and/or with 8 mm thick clear toughened glass with machine polished edges.				
iii.	Shutters shall be made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) and/or with 5 mm. thick etched glass of approved make. Each shutter shall be fixed to the framework/ carcass using three numbers of best quality EURO type Slip-in Hinges (approved make) and provided with an approved quality and profile brush finished SS handle of approved design. (minimum 100 mm long), wall catchers etc.				
iv.	Each drawer made out of 18/19 mm thick BWR plywood with ISI mark (IS 303) which shall be mounted on approved quality high precision telescopic channels of approved make (to be designed as per drawer size and weight with minimum length of 18") to ensure smooth movements and provided with approved quality SS brush finished handles (minimum 100 mm long).				
v.	The unit shall be firmly fixed to the walls/ slabs/floor using metal screws of appropriate size and rawplug / nylon sleeves.				
v.	All exposed surfaces of the plywood used in the work shall be laminated with 1 mm thick laminate of approved make and shade (factory pressed) using approved quality and make synthetic resin based adhesives.				
vi.	All Inner surfaces of the plywood used in the work shall be suitably polished in minimum two coats whereas the shutters would be laminated with 0.8mm thick laminate of approved make and shade using approved quality and make synthetic resin based adhesives.				



vii.	Edges (Top & Bottom) of the plywood shall be provided with 3.0 mm thick teak wood lipping of approved quality and using approved quality and make synthetic resin based adhesives)				
	(Note-This shall be broadly in line with the existing crockery unit / showcase provided in niche in the hall of 2 BHK Flats staircase side . Only elevation area will be measured for payment).				
6	Providing and fixing of Granite of 18 mm thick black colour (both sides polished) wherever required as per required size, moulding etc. including necessary civil works . Complete item of work	20	Per sqm		
7	DISMANTLING OF EXISTING SHUTTERS, CABINET, SHOW PIECE, CROCKERY UNIT ETC. FROM EACH FLATS INCLUDING ITS CAREFUL REMOVAL AND CARTING AWAY THE SAME UNDER BUY BACK. (Note: MINIMUM AMOUNT NOT LESS THAN RS.16,000/- CONTRACTOR CAN OFFER HIGHER AMOUNT BUT NOT LESS THAN RS.16,000/- . THE AMOUNT QUOTED HERE BY THE CONTRACTOR OR RS.16,000/- WHICH EVER IS HIGHER SHALL BE DEDUCTED FROM THEIR BILLS. CONTRACTOR SHALL TAKE FULL RESPONSIBILITY OF CARTING , TRANSPORTING, DISPOSING ALL THE TAKE AWAY ITEMS. AS DIRECTED INCLUDING MAKING GOOD THE SURFACES, NECESSARY CIVIL TOUCH UP WORKS, APPLYING PUTTY ETC. SO AS TO RECEIVE NEW WORKS).	1	LS		
	Sub Total (A)				
	Service Tax _____ % on "A" above				
	Grand Total				

Notes:



1. The sketch enclosed with the tender documents are indicative only. The successful tenderer shall submit working drawings based on actual measurements at site and get the same approved by the Bank's engineer/architect before taking up the fabrication of sample kitchen , wardrobes etc..
2. The contractor has to first prepare the sample of each item . The same will be approved by SIDBI/Architects. The contractor is required to carryout necessary modification for other flats. No extra cost would be payable for charges, if any suggested by the SIDBI/Architects.
3. The tenderers must include in their tender prices quoted for all duties, royalties, cess and sales tax/work contract tax or any other taxes or local charges, as applicable. No extra claim on this account will in any case be entertained. Applicable Service Tax (including Swatch Bharat Cess) on work contract shall be payable by SIDBI/Contractor as per the Governing law/Act in force. Contractors/ agencies/firms should submit their offer indicating service tax component separately as indicated above.
4. The applicable service tax has to be quoted separately as indicated above and L-1 Contractor will be decided on the total outgo for the Bank including Service Tax

Place:

Signature of the
Name and address of the
firm:

Date:

